

Pitch 1.0mm Double Row Pin Header SMD Series 1/2

SPECIFICATIONS

Current rating : 1 Amp

Contact Resistance : 20 Milliohms Max .

Insulation resistance : 500 Megohms Min.

Operating Temperature : - 40 C ~ + 105 C

Contact Material : Copper Alloy

Insulator Material : Thermoplastic UL 94V-0

ORDER INFORMATION:

SHPD18 - $\frac{XX}{a}$ $\frac{1}{b}$ - $\frac{1}{c}$ $\frac{2}{d}$ - $\frac{1.9/1.3}{e}$ - $\frac{BN}{fg}$ - $\frac{T}{h}$

a. Pin of numbers:

04 ~ 80

b. Plastic Base :

1 : H=1.00 mm(standard)

2 : H=1.50 mm

c. Plated selection :

0 : Tin Plated

1 : Gold Flash

2 : Gold 5u"

3 : Gold 15u"

4 : Gold 30u"

d. Post selection :

0 : Without Post

1 : With Post

2 : Without Post+CAP

3 : With Post+CAP

e. Pin length:

if you desire on other length, by marking
put desired length the A / B.

(A/B=1.90/1.30)

f. Plastic Color :

B : Black

g. Plastic material selection:

L : L.C.P

N : Nylon 6T

h. Pack selection:

C : Contron Pack

T : Tube Pack

R : Reel Pack

Pitch 1.0mm Double Row Pin Header SMD Series 2/2

