



RECOMMENDED PCB
SCALE: 1:1

- NOTES:
- ELECTRICAL :
 VOLTAGE :100V AC
 CURRENT : 0.5A Max
 CONTACT RESISTANCE : 40mΩ
 VOLTAGE PROOF : 500V AC
 INSULATION RESISTANCE : 1000MΩ
 - MECHANICAL :
 CARD INSERTION/WITHDRAWAL FORCE : 13.8N MAX
 PUSH IN STRENGTH : 19.6N
 DURABILITY : 10,000 CYCLES
 - MATERIAL :
 INSULATOR :LCP BLACK
 SHELL :SUS304
 CONTACT :COPPER ALLOR
 CONTACT AREA: GOLD FLASH PLATING

T-FLASH CARD				SIM CARD	
pin No	NAME	TYPE	DESCRIPTION	pin No	NAME
1	DAT2	I/O/PP	Date Line[bit2]	C1	VCC
2	CD/DAT3	I/O/PP	Card Detect Date Line[bit3]	C2	RST
3	CMD	PP	Commend Response	C3	CLK
4	VDD	S	Supply Voltage	C4	GND
5	CLK	I	Clock	C5	VPP
6	VSS	S	Supply Voltage Ground	C6	I/O
7	DAT0	I/O/PP	Date Line[bit0]		
8	DAT1	I/O/PP	Date Line[bit 1]		

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME
1			2			A4	1.0	1-3113-003N000

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANGLES	ANG.	±5°
LINEAR	0.	±0.3
	0.0	±0.25
	0.00	±0.20
SCALE	AS SHOWN	UNIT: mm
DRAWN	Leon	2013/03/06
CHECKED	Klasu	2013/03/06
APPROVED	John	2013/03/06

 連科電子股份有限公司 Connectec Electronics Co., Ltd.		DRAWN NAME:	
		Micro SD with SIM 2 in 1 Socket	
PRODUCT NO.		1-3113-003N000	
FILE NAME		1-3113-003N000	

- △ Revise:
- △ Revise:
- △ Revise: