


LTE-TDD/LTE-FDD/TD-SCDMA/UMTS/EDGE/GPRS/GSM/ GPS Cellular Module


U8300W is a wireless module which is designed for the global market. It is a consumptive product; it can be designed in many kinds of applications which can work on LTE-TDD/LTE-FDD/TD-SCDMA/UMTS/EDGE/GPRS/GSM network.

On LTE-TDD network, U8300W enables connect to the Internet at DL data speed up to 61Mbps and UL data speed up to 18Mbps. On LTE-FDD network at speed up to 100Mbps DL and 50Mbps UL, in the area where LTE service are not available, U8300W still enables reliable and secure data connect over 3G(TD-SCDMA/UMTS) or 2G(EDGE/GPRS) network.

U8300W provides SMS, MMS, Phonebook functions as well as high speed access, and also audio function. It can be designed in many kinds of applications. Such as Data card, Video monitor, Tablet, Electric-book, MID, Vehicle equipment, etc.



LTE-TDD/LTE-FDD




M2M application



PCI Express Mini Card Standard Interface



Receive diversity



Router application




RoHS compliance



AT Command



USB 2.0 interface




Windows XP/Vista/7 operating system




Surveillance application



UART interface



Linux operating system



Laptop application



GPS



U8300W

LTE-TDD/LTE-FDD Cellular Module

General features:

- EDGE multi-slot class 12
- GPRS multi-slot class 12
- Compliant to GSM phase 2/2+
- Output power:
 - Class 3 (0.25W) for LTE/TD-SCDMA/UMTS
 - Class 4 (2 W) for GSM850/900
 - Class 1 (1 W) for GSM1800/1900
- Control via AT commands (3GPP TS27.005/3GPP TS27.007)
- Supply voltage range 3.3V-3.6V
- Low Power consumption
 - Sleep mode: 5mA
 - Power down 50 μ A
- Dimensions: 51.0×30.0×4.6mm
- Temperature range
 - Normal Operation: -20°C to +65°C
 - Restricted Operation: -30°C to +75°C
 - Storage Operation: -40°C to +85°C

Specifications for SMS:

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Band Configuration:

U8300W:

- LTE-TDD Quad-band
 - Band 38/39/40/41
- LTE-FDD Tri-band Band 1/3/5
- TD-SCDMA Dual-band Band 34/39
- UMTS Dual-band Band 1/5
- GSM Quad-band 850/900/1800/1900

Specifications for GPS:

- Support 55 channel
- TTFF
 - Cold Start: 32S
 - Warm Start: 29S
 - Hot Start: 1S
- Sensitivity
 - Cold Start: -145dBm
 - Acquisition: -160dBm
 - Tracking: -161dBm

Additional features:

- Phone book
- PCM and analog Audio
- DTMF

Approvals:

- RoHS
- CCC
- CTA

Specifications for data:

- Support Release 9 Category 3
- LTE-FDD up to 100 Mbps DL, 50 Mbps UL
- LTE-TDD up to 61 Mbps DL, 18 Mbps UL
- TD-SCDMA up to 4.2 Mbps DL, 2.2 Mbps UL
- DC-HSPA+ up to 42Mbps DL, 5.76Mbps UL
- EDGE class 12: 237kbps DL, 118kbps UL
- GPRS class 10: 85.6kbps DL, 85.6kbps UL
- CSD up to 14.4 kbps
- Non transparent mode
- PBCCH support
- PPP-stack
- Coding schemes CS 1,2,3,4
- FOTA
- TCP/IP
- NDIS

Interfaces:

- RF connector
- PCI Express® Mini Card Interface
 - Power supply
 - USB 2.0 high speed
 - UICC/SIM/UIM card interface 3 V, 1.8 V
 - UART
 - Analog Audio
 - PCM
- Antenna connector